



Product Specification Sheet

BuzziPleat Light EU












— By 13&9 Design

An avant-garde solution

BuzziPleat Light delivers exceptional sound control with an architectural edge thanks to its architectural folds made from our hero material, BuzziFelt. The suspended lighting solution can be equipped with BuzziSol, a powerful LED light source, or a retrofit option.



The Family

		Models		
Lighting Units	Retrofit E27 (bulb excluded)	BuzziPleat Light Edel	BuzziPleat Light Edel Long	BuzziPleat Light Ripple
				
	LED Solo Globe			
	LED Solo Spot			
	LED Trio Globe			
	LED Trio Spot			
	LED Quintet Globe			
	LED Quintet Spot			

Required order information

1. Model
2. Size
3. BuzziFelt Color
4. Option Extra Layer BuzziFabric
5. Light Option
6. Mounting System
7. Color Lace

Lighting Data

Lighting Units



Retrofit Lighting unit



BuzziSol Solo retrofit includes 1 x E27 fitting. (max.40W)
BuzziSol Trio retrofit includes 3 x E27 fitting. (max.60W)
Bulb Excluded


LED

Globe



BuzziSol is a LED fixture consisting of 1 (BuzziProp Small) or 3 (BuzziProp Beam) powder-coated black heatsink with LED chip on board (COB) light source(s).
The product can be finished with a frosted glass globe diffuser which spreads the light in a large beam angle of 170°, enlighting the surroundings or a reflector spot adaptor directing the light with a beam angle of 38° downwards.

Spot



BuzziPleat Light

**Model: Edel | Ripple
Medium | Large**

Lighting Options

Characteristics

Mounting

Lighting Unit	Voltage Input	Technical	Visual	Options
Retrofit Solo	220-240V	Wattage: Max. 40W	Color: Power Cable: Black Ceiling Canopy: Black	

Lighting Options

Characteristics

Mounting

Lighting Unit	Voltage Input	Color Temperature	UGR (Diffuser type)	Dimming	Technical	Visual	Options
LED Solo	220-240V	2700K 3000K 4000K	23 (Globe)	1-10V DALI	Power consumption: 20W Light output: 1500 Lm Efficacy: 75 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	
			12 (Spot)	1-10V DALI	Power consumption: 20W Light output: 1500 Lm Efficacy: 75 Lm/W CRI: >w 90		

Model: Light Edel Long Medium

Lighting Options

Characteristics

Mounting

Lighting Unit	Voltage Input	Technical	Visual	Options
Retrofit Trio	220 - 240V	Wattage: 3 x Max. 60W	Color: Power Cable: Black Ceiling Canopy: Black	2 cables of 2 m or 5 m Alu or Black

Lighting Options

Characteristics

Mounting

Lighting Unit	Voltage Input	Color Temperature	UGR (Diffuser type)	Dimming	Technical	Visual	Options
LED Trio	220 - 240V	2700K 3000K 4000K	23 (Globe)	1-10V DALI	Power consumption: 60W Light output: 3 x1500 Lm Efficacy: 92 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	2 cables of 2 m or 5 m Alu or Black
			12 (Spot)	1-10V DALI	Power consumption: 60W Light output: 3 x1500 Lm Efficacy: 92 Lm/W CRI: > 90		

Model: Light Edel Long Medium

Lighting Options

Characteristics

Mounting

Lighting Unit	Voltage Input	Color Temperature	UGR (Diffuser type)	Dimming	Technical	Visual	Options
LED Quintet	220 - 240V	2700K 3000K 4000K	23 (Globe)	1-10V DALI	Power consumption: 90W Light output: 5 x 1500 Lm Efficacy: 92 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	2 cables of 2 m or 5 m Alu or Black
			12 (Spot)	1-10V DALI	Power consumption: 90W Light output: 5 x 1500 Lm Efficacy: 92 Lm/W CRI: > 90		




CE CB


Photometric Data

BuzziPleat Light BuzziSol Solo


LED Solo Globe Cartesian diagram




LED Solo Globe Polar curve



LED Spot Cartesian diagram




LED Spot Polar curve




BuzziPleat Light BuzziSol Trio


LED Trio Globe Cartesian diagram




LED Trio Globe Polar curve



LED Trio Spot Cartesian diagram




LED Trio Spot Polar curve




BuzziPleat Light BuzziSol Quintet


LED Quintet Globe Cartesian diagram




LED Quintet Globe Polar curve



LED Quintet Spot Cartesian diagram



LED Quintet Spot Polar curve




Tips and Tricks - Light Options

To enlight your workplace with optimal lux levels take following measurements into account:

BuzziPleat Light BuzziSol Solo


Solo Spot

Office,
Meeting room



Solo Globe


Office,
Meeting room



BuzziPleat Light BuzziSol Trio


Trio Spot

Office,
Meeting room



Trio Globe


Office,
Meeting room



BuzziPleat Light BuzziSol Quintet


Quintet Spot

Office
Meeting room



Quintet Globe

Office,
Meeting room




* According to EN12464

Product Data

Fixing System

Fixing System Acoustic Panel



BuzziPleat Light Edel and Ripple are suspended on 3 cables of 2 or 5 m black or alu colored cables, with fixing system screw.

BuzziPleat Light Edel Long is suspended on 4 cables of 2 or 5 m black or alu colored cables, with fixing system screw.

Fixing System Lighting

The light element of BuzziPleat Light Edel Long is suspended independently from the acoustic panel with 2 cables of 2 – 5 m black or alu colored cables, with fixing system screw.

▲ If installing on suspended ceiling, verify load capacity prior to installation.
Ensure a min distance of 10 cm between the felt shade and the LED luminaire.


Acoustic Panel



The acoustic panel consists of one layer of BuzziFelt, with an OffWhite or Black lace.

The lightweight sculptural shade is created by pleating or smocking sound absorbing BuzziFelt.

The architectural folds maximize surface area, delivering exceptional acoustic performance.




Optional: an extra layer of BuzziFabric can be added on 1 side (only in combination with OffWhite or Anthracite Felt).

Acoustics Data

BuzziPleat Ceiling Suspended


Equivalent sound absorption area in m² per object




Hz	Edel M Aeq/m²	Edel L Aeq/m²	Edel Long M Aeq/m²	Ripple M Aeq/m²	Ripple L Aeq/m²
125	0.18	0.54	0.58	0.14	0.20
250	0.32	0.92	0.87	0.39	0.50
500	0.63	1.64	1.49	0.92	0.90
1000	0.94	2.13	2.48	1.19	1.30
2000	1.11	2.56	2.80	1.39	1.40
4000	1.30	2.75	2.92	1.59	1.70

Dimensions

BuzziPleat Light Ripple LED




BuzziPleat Light Ripple Retrofit




Height	M	13 cm
	L	19,5 cm


Width	M	Ø 100 cm
	L	Ø 150 cm



BuzziPleat Light Edel LED




BuzziPleat Light Edel Retrofit




Height	M	9 cm
	L	13,5 cm



Width	M	Ø 100 cm
	L	Ø 150 cm




BuzziPleat Light Edel Long Trio LED



BuzziPleat Light Edel Long Trio Retrofit





BuzziPleat Light Edel Long Quintet




Weights


BuzziPleat Light Ripple Medium | Large BuzziSol Solo Retrofit




 Medium: 6.3 kg
Large: 12 kg


BuzziPleat Light Ripple Medium | Large BuzziSol Solo LED




 Medium: 6,7 kg
Large: 12,4 kg


BuzzuPleat Light Edel Medium | Large BuzziSol Solo Retrofit




 Medium: 5,3 kg
Large: 10 kg


BuzzuPleat Light Edel Medium | Large BuzziSol Solo LED




 Medium: 5,7 kg
Large: 10,4 kg


BuzziPleat Light Edel Long Trio BuzziSol Trio Retrofit




 11.6 kg


BuzziPleat Light Edel Long Trio BuzziSol Trio LED



 14 kg

BuzziPleat Light Edel Long Quintet BuzziSol Quintet LED



 16,5 kg


Fabrics

Felt


Composition 100% Recycled P.E.T. Felt
Weight 1.000 g/m² | 29.49 oz/yd²
Abrasion resistance >7.000 Martindale
Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0
USA: ASTM E84 Class A certified
Fastness to light USA 5



FE-OffWhite 63*




FE-StoneGrey 67



FE-Anthracyte 68*

*Extra layer BuzziFabric Possible

Fabric (45 colors)




Category A
Composition 70% Recycled Wool, 25% Recycled Polyacryl,
5% Recycled Other Fabrics
Weight 405 g/m² | 11.94 oz/yd²
Abrasion resistance 40.000 Martindale, 50,000 Wyzenbeek
Flammability EU: EN 1021.1/2006 | BS EN 1021.1/2006 (cigarette).
EN 1021.2/2006 | BS EN 1021.2/2006 (match)
USA: CAL TB 117 | ASTM E84 CLASS A
Fastness to light EU: 4 | USA 4
Fastness to rubbing EU: Wet 3-4 | Dry 4-5
Fastness to crocking USA: Wet 5 | Dry 5



Acoustics

BuzziPleat Ceiling

Equivalent sound absorption area in m² per object



Hz	Edel M Aeq/m²	Edel L Aeq/m²	Edel Long M Aeq/m²	Ripple M Aeq/m²	Ripple L Aeq/m²
125	0.18	0.54	0.58	0.20	0.50
250	0.32	0.92	0.87	0.50	1.50
500	0.63	1.64	1.49	0.90	2.40
1000	0.94	2.13	2.48	1.20	2.80
2000	1.11	2.56	2.80	1.40	3.20
4000	1.30	2.75	2.92	1.60	3.50