



Executive armchair with high or medium back, with armrests and backrest handle in polished aluminium.

Seat & Backrest

Seat and backrest bearing in support soft Eurolene thickness 1.3 mm;

Padding in polyurethane foam of density 60 kg/m³, with thickness 1,5 cm coated and sewn with stitching in horizontal stripes, applied with velcro to the support.

Frame

Frame without visible screws in high-strength steel, round section Ø 25 mm for 1.5 mm thick chrome or black painted finish. Rear handle, closing caps and armrests in polished or black painted aluminium.



Mechanism

M5 Tilt mechanism with gas height adjustment and locking in the operating position. It is complete with handwheel for the variation of the oscillation hardness.

M5B Tilt mechanism in polished aluminium, with gas height adjustment and locking in the operating position. It is complete with handwheel for the variation of oscillation hardness. The bearing shell is entirely built in black painted aluminum.

M5A Tilt and self-weighing synchron mechanism with a single lever polished aluminum, with gas height adjustment and locking in operating position. The bearing shell is entirely made of polished aluminium.

M4 /M3 Advanced tilt mechanism the point of rotation of this mechanism is placed further ahead than the standard. The locking lever allows locking in 3 positions with self-return system of the seat. It is complete with handwheel for the variation of the oscillation hardness. The load-bearing shell is entirely made of polished or black painted die-cast aluminium.

M10 Armonico tilt mechanism, guarantees a permanent oscillation of the seat and gas lift.

M8 swivel plate with elevation

Base

Leggera base in polished or black painted aluminium with 5-spoke on wheels [d. 680 mm]

Shop base in polished or black painted aluminium with 4-spoke on feet [d. 680 mm]

Standard black nylon double tread wheels with 65 mm diameter.

Accessories

Armrest cover with slightly padded and coated metal support. Available in two versions.



Product's certificates



Measures	Seat height	Total height	Width	Depth
cm	52/60	107/115	48/70	47/72
cm	52/60	91/99	48/70	47/72

LASER

GRADE 2

560 gr/mtl
100% Polyester FR
Classe 1
80.000+/- 10% cicli Maltindale

ECOPELLE

GRADE 2

630 g/lin.m
83% PVC 17% Synthetic
Classe 1
30.000 +/- 10% cicli Maltindale

JET

GRADE 3

365+/- 5% g/lin.m
100% Polyester FR
Classe 1
80.000+/- 10% cicli Maltindale

ONE RECICLED

GRADE 3

525 gr/mt2
100% recycled poliester
CLASSE 11M
100.000 CICLI

LYRA

GRADE 3

550 g/lin.m
100% Polyester
Classe 1
60.000 +/- 10% cicli Maltindale

CHILI

GRADE 3

470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- cicli Maltindale

DREAM

GRADE 3

375gr/mtl
100% Polyester solution dyed
melange bouclè effect
OEKO TEST
Classe1 - 100.000 +/- cicli Maltindale

MELANGE

GRADE 3

390 g/lin.m
100% Trevira CS
Classe 1
80.000 +/- 10% cicli Maltindale

VELOURS

GRADE 3

611 gr/mtl
100% Polyester
Oeko test
50.000 +/- 10% cicli Maltindale

ECOPELLE SOUL

GRADE 3

760 gr/mt2
Surface 100% POLIURETANO,
Base Polyester 85%,17% Cotton
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

COCOON

GRADE 5

980 gr/mtl
43% viscose 33% cotton 24% li-pl
35.000 +/- 10% cicli Maltindale

LANA

GRADE 5

500 gr/mt2
75% Wool, 25% polyamide
Classe 1
100.000 cicli Maltindale

GLAMOUR

GRADE 5

700 g/lin.m
100% Polyester Recycled
EN 1021-1/2
80.000 % cicli Maltindale

TECHNICOLOUR livvadrat

GRADE 5

430 g/lin. M
100% new English wool, worsted
80.000 % cicli Maltindale
Ecolabel
Classe 1

MAIN LINE candira

GRADE 5

437 g/lin.m
75% Virgin wool, 25% Linen
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

PELLE

GRADE 5/6

620 g/lin.m
100% Cowhide
Classe 1, EN 1021-1/2

PELLE PREMIUM UP/ELEGANCE

GRADE 7

100% first flower cowhide
Width 1,2/1,4 mm
EN1021-1/2

MONOCHROME SETT candira

GRADE 7

437 g/lin.m
75% Virgin wool, 25% Linen
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

BOUCLET livvelli

GRADE 7

860 g/lin.m
40% PC, 25%PL,20%VI, 15% CO
Classe 1, EN 1021-1/2
50.000 % cicli Maltindale

VELLUTO DECONTRACTE' livvelli

GRADE 7

590 g/lin.m
19% CO, 61% PC,10% PL, 10% VI
40.000 % cicli Maltindale

HORO livvelli

GRADE 7

495 g/lin.m
44%PL 29%CO 24%JU 3%PC
30.000 % cicli Maltindale

PELLE SETA

GRADE 8

100% Cowhide width1,8-2 mm
first-grain leather
EN1021-1/2

ZERO

GRADE 8

750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % cicli Maltindale

Disassemblability

All products have been designed in such a way that they can be disassembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Guarantee and safety

QUINTI guarantees that the products will keep their characteristics for 6 years from delivery, save normal wear and provided they are used according to the indications given. QUINTI will replace any product found not to comply with this warranty at no cost, without bearing any other responsibility. The application of the component warranty is excluded; external accessories or materials provided by the buyer and applied to products for the purpose of a customization of the same. For optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are required.

All the sessions offered are SAFE according to the provisions of the EU Regulation 2023/988, on general product safety (GPSR), reinforced by UNI EN certifications.

The company is not liable for misuse (Stand up or use products such as ladders and oscillations that could affect the operation and safety of the user. To lift or move the product, grasp firmly on the supporting structure. The product must not be subjected to decentralized loads, is designed to be used in normal standing conditions on 4 legs or on the base).

Use & Maintenance

For an optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

THE TEXTILES

Cleaning: consult the recommendations for maintenance and washing given in the fabric sheet of the color chart. Use: It is recommended to pay attention to the use as it can be torn or cut.

THE LEATHERS

Cleaning: clean with a damp white cloth soaked in water only. Use high-quality leather care products according to the manufacturer's instructions. In case of doubt, test the product on a part hidden from view to verify the result, waiting at least 24 hours for possible problems. Use: remember that the leather is a delicate material therefore it is recommended to take care during use.

THE METALS

Cleaning: both metal surfaces made of steel or aluminium, as well as painted surfaces, must be cleaned with a damp and soft cloth soaked in hot water. For the most stubborn stains, you can dilute liquid neutral soap in water with moderation. Always dry after cleaning with a soft cloth or deer leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and sponges that can scratch metal surfaces. Use: be careful of food stains such as coffee, cola, fruit juices that can leave indelible stains on surfaces.